

## 5800 Transmitters

DOOR/WINDOW TRANSMITTERS



The 5800 Series of door and window transmitters provide the most reliable, convenient and cost effective solutions for security protection. These devices are powerful and versatile enough to help solve even the toughest, most labor intensive installations.

With a demonstrated outdoor range of over a mile, the 5800 Series has the best performance of any transmitters available today.

### FEATURES

#### 5814 Ultra Small Door/Window Transmitter

The 5814 provides the perfect solution for difficult to reach places and applications where aesthetics and small size are important.

- Ideal for ornate doors/windows, casements, etc.
- Extremely compact
- Features a built-in reed switch and tamper
- Includes replaceable lithium coin cell battery
- Dimensions: 1-1/2" H x 1-3/16" W x 5/8" D

#### 5815 Door/Window Transmitter

The 5815 is the ideal solution for installations where small size and aesthetics are important. It provides a reliable, convenient and cost-effective solution for door and window protection.

- New sleek design
- Two reed switches
- Transmits supervisory, tamper and low battery messages
- Battery: 3V Lithium
- Dimensions: 3" H x 1-1/2" W x 7/8" D

#### 5816 Door/Window Transmitter

Two zone transmitter with both built-in magnetic reed switches and wired closed circuit contact loop.

- Features a standard white plastic case. Brown cases available in packs of three (5816BR).
- Dimensions: 3-1/16" H x 1-9/16" W x 1-3/16" D
- Four pack of spare magnets (5899)

#### 5816MN Door/Window Transmitter

Two zone transmitter with both built-in magnetic reed switches [90° apart] and wired closed circuit contact loop.

- Features a small design for a hidden professional look
- Dimensions: 3-1/16" H x 1-1/2" W x 15/16" D

# 5800 Transmitters

## DOOR/WINDOW TRANSMITTERS

### FEATURES

#### 5817 Three Zone Universal Transmitter

Three zone transmitter with three separate contact loops. Primary loop supports normally open and normally closed applications and fast loop response time. The two auxiliary loops support conventional normally closed contact applications.

- Features a normal zone response time of 200msec; the fast zone response is 5msec
- Dimensions:  
3-1/2" H x 1-9/16" W x 1-3/16" D

#### 5817CB Universal Contact-Monitoring Transmitter

The 5817CB is a universal contact-monitoring transmitter that can be used with household and commercial fire and burglary-initiating devices.

- The 5817CB has three unique input loops (zones)

- The first loop (primary loop) is supervised and typically used for high-priority alarm reporting such as commercial fire or burglary
- The second loop is the built-in, normally closed reed switch used in conjunction with magnet
- The third loop is another normally closed household burglary loop. All three loops may be used.
- A fourth (automatically enrolled) loop contains two tamper switches to protect the 5817CB
- Dimensions:  
3-1/2" H x 1-9/16" W x 1-3/16" D

#### 5818MNL Recessed Door/Window Transmitter

The 5818MNL is a magnetic contact sensor that provides concealed protection for doors or windows.

- Includes self-contained transmitter and reed sensor
- Virtually disappears once installed

- Easy replaceable AAA Lithium battery
- 0.5" gap (transmitter to magnet)
- Features a tapered cylinder for easy and flush fit
- Dimensions:  
0.75" diameter x 3.0" length

#### 5820L Door/Window Contact Transmitter

The 5820L is nearly half the size of standard door/window transmitters. It is ideal for casement and double-hung windows.

- Sleek design is nearly half the size of competitors
- Case tamper protection (front and back)
- Ideal for double-hung windows
- Easy replaceable AAA Lithium battery
- Dimensions:  
3.0" H x 0.5" W x 0.8" D

### ORDERING

<b>5814</b>	Ultra Small Door/Window Transmitter
<b>5815</b>	Door/Window Transmitter
<b>5816MN</b>	Door/Window Transmitter
<b>5816</b>	Door/Window Transmitter
<b>5817</b>	Three Zone Universal Transmitter
<b>5817CB</b>	Three Zone Universal Transmitter
<b>5818MNL</b>	Recessed Door Transmitter with Lithium battery supplied
<b>5820L</b>	Slimline Door/Window Contact Transmitter supplied with Lithium battery
<b>5899</b>	Four pack of spare magnets for 5816

**Automation and Control Solutions**  
Honeywell Security & Communications  
2 Corporate Center Dr. Suite 100  
P.O. Box 9040  
Melville, NY 11747  
www.honeywell.com

L/5800TRAN/D  
January 2009  
© 2009 Honeywell International Inc.

**Honeywell**